

(12) United States Patent Hughes

(45) **Date of Patent:**

(10) Patent No.:

US 7,383,946 B2

Jun. 10, 2008

(54) MATERIALS FOR STORING AND RELEASING REACTIVE GASES

(76) Inventor: Kenneth D. Hughes, 765 Bellemeade

Pl., Alpharetta, GA (US) 30004

Subject to any disclaimer, the term of this Notice:

patent is extended or adjusted under 35

U.S.C. 154(b) by 243 days.

(21) Appl. No.: 11/089,678

Mar. 25, 2005 (22)Filed:

(Under 37 CFR 1.47)

(65)**Prior Publication Data**

> US 2005/0235830 A1 Oct. 27, 2005

Related U.S. Application Data

- Provisional application No. 60/557,146, filed on Mar.
- (51) Int. Cl. C01B 11/02 (2006.01)B01J 20/26 (2006.01)
- (52) U.S. Cl. 206/0.7; 210/660
- 95/132; 96/108; 210/660, 668, 679; 206/0.6, 206/0.7; 222/3; 252/181.1, 60; 205/556;

See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

286,370 A	10/1883	Baker
3,238,056 A	3/1966	Pall et al.
3,344,061 A	9/1967	Kellum
3,375,933 A	4/1968	Rodman
3,442,796 A	5/1969	Hayes
3,545,622 A	12/1970	Sakhonvsky

3,662,893 A	5/1972	Humbert
3,871,881 A	3/1975	Mikelsons
3,996,131 A	12/1976	Conn
4,078,112 A	3/1978	Bibeau
4,079,001 A	3/1978	Haase et al.
4,084,747 A	4/1978	Alliger
4,098,690 A	7/1978	Semmens
4,160,727 A	7/1979	Harris
4,167,479 A	9/1979	Besik
4,178,361 A	12/1979	Cohen et al.
4,182,676 A	1/1980	Casolo
4,190,576 A	2/1980	Thomson et al.
4,194,040 A	3/1980	Breton et al.
4,198,296 A	4/1980	Doumas et al.
	(6	1)

(Continued)

FOREIGN PATENT DOCUMENTS

FR 2790767 A1 9/2000

(Continued)

Primary Examiner—Frank M. Lawrence (74) Attorney, Agent, or Firm-Sutherland Asbill & Brennan LLP

(57)**ABSTRACT**

Compositions, methods, and devices are provided for use in containing and releasing a gas, particularly a reactive gas. The composition can include a reactive gas, reactive gas precursor, or combination thereof; a fluid in which the reactive gas, reactive gas precursor, or combination thereof is dissolved; and a solid material (e.g., particles or fibers) in which fluid is absorbed or adsorbed, wherein the solid material controls the formation or release of the reactive gas. The materials and methods allow rapid and safe generation, transfer, and application of high concentrations of chlorine dioxide gas in solid, liquid, and gas phase systems and are suitable for a variety of chlorine dioxide applications, such as disinfecting and sanitizing liquids, solid surfaces, and porous materials.

12 Claims, 3 Drawing Sheets

